

		STATOR															ROTOR							
Size	Model	CONFIGURATION					FIT @ 75° F (Inch)										Minor Diameter Tolerance +/-	CONFIGURATION						
		Tube OD/ID Inch	Length Inch	Cutback Inch	Lobes	Stages	NBR					NBR - HPW/HPX						Overall Length Inch	Contour Length Inch	Ecc Inch	Major Diameter Inch	Head Diameter Inch	Thread Connection	Weight lb
							STD	.50S	10S	1.50S	20S	STD	.50S	10S	1.50S	20S								
1 11/16"	AT168562.3	1.69/1.38	60.00	4.00/4.00	5/6	2.3	0.003	-	-	-	-	0.003	-	-	-	-	0.010	55.00	51.00	0.076	1.063	1.000	N/A	11
	AT168565.0	1.69/1.38	99.00	4.00/4.00	5/6	5.0	0.001	-	-0.009	-	-	0.001	-	-0.009	-	-	0.010	93.00	87.00	0.069	0.990	1.100	N/A	16
2 1/8"	AT212566.0	2.13/1.75	88.00	4.00/4.00	5/6	6.0	0.003	-	-	-	-	0.003	-	-	-	-	0.010	83.13	79.00	0.087	1.236	1.250	N/A	21
2 3/8"	AT237784.0	2.38/1.88	82.00	4.00/4.00	7/8	4.0	0.000	-	-0.012	-	-	0.000	-	-0.012	-	-	0.010	79.20	75.00	0.082	1.500	1.500	N/A	32
2 7/8"	AT287454.0	2.88/2.38	105.63	4.00/4.00	4/5	4.0	-	0.006	-	-	-	-	0.006	-	-	-	0.010	103.63	99.63	0.156	1.843	1.800	N/A	56
	AT287563.5	2.88/2.38	98.60	7.00/7.00	5/6	3.5	0.007	-	-	-	-	0.007	-	-	-	-	0.010	91.00	86.50	0.118	1.675	1.800	N/A	44
	AT287564.7	2.88/2.38	105.63	4.00/16.00	5/6	4.7	-0.003	-	-0.013	-0.033	-	0.001	-	-0.009	-0.031	-	0.010	92.00	88.00	0.136	1.909	1.880	N/A	58
	AT287567.0	2.88/2.38	117.00	8.00/8.00	5/6	7.0	0.002	-	-	-	-	0.007	-	-	-	-	0.010	110.00	106.00	0.122	1.658	1.650	N/A	51
3 1/8"	AT312563.5	3.13/2.63	88.00	4.00/4.00	5/6	3.5	-0.007	-	-0.018	-	-	-0.005	-	-0.016	-	-	0.010	86.00	82.00	0.156	2.174	2.175	N/A	69
	AT312565.0	3.13/2.63	106.00	5.63/5.63	5/6	5.0	-0.005	-	-0.015	-	-	-0.003	-	-0.013	-	-	0.010	101.50	97.00	0.148	2.073	1.850	N/A	74
	AT312782.5	3.13/2.63	99.88	7.00/7.00	7/8	2.5	-0.006	-	-0.017	-	-	-0.004	-	-0.015	-	-	0.010	93.00	86.50	0.122	2.120	2.060	N/A	75
	AT312783.0	3.13/2.63	106.00	5.00/5.00	7/8	3.0	0.003	-	-0.006	-	-	0.003	-	-0.006	-	-	0.010	101.00	97.00	0.109	1.971	2.000	N/A	72
3 3/8"	AT337563.2	3.38/2.75	94.00	7.00/7.00	5/6	3.2	0.002	-	-0.005	-	-	0.004	-	-0.003	-	-	0.010	90.00	84.00	0.161	2.228	2.250	N/A	74
3 1/2"	AT350453.2	3.50/2.88	100.00	6.00/6.00	4/5	3.2	0.002	-	-0.008	-	-	0.004	-	-0.006	-	-	0.010	97.00	91.00	0.185	2.245	2.250	N/A	78
	AT350563.0	3.50/2.75	80.00	6.00/6.00	5/6	3.0	-0.006	-	-0.026	-	-	-0.002	-	-0.022	-	-	0.010	76.25	72.25	0.134	2.157	2.000	N/A	62
4 3/4"	AT475456.0	4.75/3.75	187.00	8.00/8.00	4/5	6.0	-0.002	-	-0.020	-	-	0.000	-	-0.018	-	-	0.010	179.00	173.00	0.246	2.912	2.750	2.375 HEF Modified	244
	AT475456.3	4.75/3.75	207.00	8.00/8.00	4/5	6.3	-0.002	-0.011	-0.020	-0.029	-	0.000	-0.009	-0.018	-0.027	-	0.010	188.00	182.00	0.246	2.912	2.750	2.375 HEF Modified	256
	AT475459.7	4.75/3.88	235.00	8.00/15.50	4/5	9.7	-0.004	-0.014	-0.024	-0.034	-	0.000	-0.010	-0.020	-0.030	-	0.011	214.75	208.25	0.226	2.822	3.000	2.375 HEF Modified	278
	AT475568.3	4.75/3.75	242.50	8.00/8.00	5/6	8.3	0.012	0.002	-0.009	-0.024	-0.041	0.014	0.004	-0.007	-0.022	-0.039	0.010	229.50	223.00	0.207	2.916	3.125	2.375 HEF Modified	333
	AT475782.0	4.75/3.75	180.00	8.00/8.00	7/8	2.0	0.004	-	-0.013	-	-	0.007	-	-0.010	-	-	0.010	172.50	166.50	0.163	2.798	2.750	2.375 HEF Modified	239
	AT475782.2 SLOW	4.75/3.75	198.00	8.00/8.00	7/8	2.2	-0.001	-0.010	-0.021	-0.031	-0.041	0.002	-0.008	-0.019	-0.029	-0.038	0.010	191.00	185.00	0.161	2.805	2.825	1.375-6 SA	270
	AT475782.6 ESX	4.75/3.75	229.25	8.00/8.00	7/8	2.6	-0.005	-0.017	-0.027	-0.037	-0.043	-0.002	-0.014	-0.024	-0.034	-0.041	0.010	220.00	214.25	0.174	3.095	2.750	2.375 HEF Modified	381
	AT475782.9	4.75/3.75	250.00	8.00/8.00	7/8	2.9	-0.004	-0.014	-0.024	-0.030	-	-0.002	-0.012	-0.022	-0.028	-	0.010	242.00	236.00	0.163	2.798	2.850	2.375 HEF	339
	AT475783.7	4.75/3.88	235.00	8.00/15.50	7/8	3.7	0.000	-0.010	-0.020	-0.030	-	0.004	-0.006	-0.016	-0.025	-	0.010	214.75	208.25	0.177	3.122	3.250	1.375-6 SA	377
	AT475783.8	4.75/3.75	187.00	8.00/8.00	7/8	3.8	0.016	0.006	-0.004	-0.015	-0.035	0.019	0.009	-0.001	-0.012	-0.032	0.010	178.00	172.25	0.163	2.945	2.750	2.375 HEF Modified	283
	AT475784.5 SX	4.75/3.75	229.25	8.00/8.00	7/8	4.5	-0.001	-	-0.021	-	-	0.002	-	-0.018	-	-	0.010	220.00	214.30	0.172	3.091	2.750	2.375 HEF Modified	381
	AT475785.0 RM	4.75/3.88	198.00	8.00/8.00	7/8	5.0	0.003	-0.007	-0.017	-0.027	-0.037	0.005	-0.005	-0.015	-0.025	-0.035	0.010	186.00	180.00	0.171	3.041	2.750	2.375 HEF Modified	311
	AT475785.0 WF	4.75/3.88	198.00	8.00/8.00	7/8	5.0	0.001	-0.009	-0.019	-0.029	-	0.003	-0.007	-0.017	-0.027	-	0.010	186.00	180.00	0.169	3.041	2.750	2.375 HEF Modified	316
	AT475786.4	4.75/3.88	235.00	8.00/8.00	7/8	6.4	-	-0.008	-	-	-	-	-0.005	-	-	-	0.010	226.00	220.00	0.170	3.029	3.250	1.375-6 SA	372
5"	AT500239.0	5.00/3.75	200.00	8.00/8.00	2/3	9.0	-	-	-0.060	-	-	-	-	-0.057	-	-	0.010	194.00	188.00	0.224	2.537	2.600	2.375 HEF Modified	183
	AT500456.0	5.00/3.75	187.00	8.00/8.00	4/5	6.0	-0.002	-	-0.020	-	-	0.000	-	-0.018	-	-	0.010	179.00	173.00	0.246	2.912	2.750	2.375 HEF Modified	244
	AT500456.3	5.00/3.75	207.00	8.00/8.00	4/5	6.3	-0.002	-0.011	-0.020	-0.029	-	0.000	-0.009	-0.018	-0.027	-	0.010	188.00	182.00	0.246	2.912	2.750	2.375 HEF Modified	256
	AT500459.7	5.00/3.88	235.00	8.00/15.50	4/5	9.7	-0.004	-0.014	-0.024	-0.034	-	0.000	-0.010	-0.020	-0.030	-	0.011	214.75	208.25	0.226	2.822	3.000	2.375 HEF Modified	278
	AT500563.7 Hi Flow	5.00/4.00	250.00	8.00/15.50	5/6	3.7	0.012	-	-0.008	-	-	0.015	-	-0.005	-	-	0.010	229.75	223.25	0.235	3.120	3.250	1.375-6 SA	318

Size	Model	STATOR																ROTOR						
		CONFIGURATION					FIT @ 75° F (Inch)										Minor Diameter Tolerance +/-	CONFIGURATION						
		Tube OD/ID Inch	Length Inch	Cutback Inch	Lobes	Stages	NBR					NBR - HPW/HPX						Overall Length Inch	Contour Length Inch	Ecc Inch	Major Diameter Inch	Head Diameter Inch	Thread Connection	Weight lb
5"	AT500566.7	5.00/4.00	250.00	8.00/8.00	5/6	6.7	0.007	-	-0.013	-0.023	-	0.010	-	-0.010	-0.020	-	0.010	241.00	235.00	0.235	3.120	2.900	2.375 HEF Modified	383
	AT500568.3	5.00/3.75	242.50	8.00/8.00	5/6	8.3	0.012	0.002	-0.009	-0.024	-0.041	0.014	0.004	-0.007	-0.022	-0.039	0.010	229.50	223.00	0.207	2.916	3.125	2.375 HEF Modified	333
	AT5006710.0	5.00/4.00	275.00	8.00/16.00	6/7	10.0	-0.007	-0.016	-0.029	-	-	-0.003	-0.014	-0.025	-	-	0.010	266.00	260.00	0.192	3.256	3.400	2.875 HEF Modified	496
	AT500676.0	5.00/4.00	185.00	8.00/8.00	6/7	6.0	-0.011	-	-0.031	-	-0.056	-0.009	-	-0.029	-	-0.054	0.010	179.50	173.50	0.192	3.018	2.900	2.375 HEF Modified	282
	AT500678.0	5.00/4.00	250.00	8.00/8.00	6/7	8.0	-0.011	-0.021	-0.031	-0.041	-0.056	-0.009	-0.019	-0.029	-0.039	-0.054	0.010	241.00	235.00	0.192	3.018	2.900	2.375 HEF Modified	383
	AT500678.8	5.00/4.00	275.00	8.00/8.00	6/7	8.8	-0.006	-0.018	-0.030	-0.037	-0.044	-0.002	-0.014	-0.026	-0.033	-0.040	0.010	265.00	258.00	0.217	3.298	3.400	2.375 HEF Modified	496
	AT500679.0	5.00/4.00	250.00	8.00/8.00	6/7	9.0	-0.004	-0.014	-0.024	-0.034	-0.044	0.000	-0.010	-0.020	-0.030	-0.040	0.010	241.00	235.00	0.194	3.190	3.250	2.375 API REG	378
	AT500782.0	5.00/3.75	180.00	8.00/8.00	7/8	2.0	0.004	-	-0.013	-	-	0.007	-	-0.010	-	-	0.010	172.50	166.50	0.163	2.798	2.750	2.375 HEF Modified	239
	AT500782.2 SLOW	5.00/3.75	198.00	8.00/8.00	7/8	2.2	-0.001	-0.010	-0.021	-0.031	-0.041	0.002	-0.008	-0.019	-0.029	-0.038	0.010	191.00	185.00	0.161	2.805	2.825	1.375-6 SA	270
	AT500782.6 ESX	5.00/3.75	229.25	8.00/8.00	7/8	2.6	-0.005	-0.017	-0.027	-0.037	-0.043	-0.002	-0.014	-0.024	-0.034	-0.041	0.010	220.00	214.25	0.174	3.095	2.750	2.375 HEF Modified	381
	AT500782.9	5.00/3.75	250.00	8.00/8.00	7/8	2.9	-0.004	-0.014	-0.024	-0.030	-	-0.002	-0.012	-0.022	-0.028	-	0.010	242.00	236.00	0.163	2.798	2.850	2.375 HEF	339
	AT500783.0 ESX	5.00/4.00	250.00	16.00/8.00	7/8	3.0	-0.008	-0.018	-0.028	-	-	-0.006	-0.016	-0.026	-	-	0.010	233.50	227.00	0.180	3.258	3.400	1.375-6 SA	457
	AT500783.7	5.00/3.88	235.00	8.00/15.50	7/8	3.7	0.000	-0.010	-0.020	-0.030	-	0.004	-0.006	-0.016	-0.025	-	0.010	214.75	208.25	0.177	3.122	3.250	1.375-6 SA	377
	AT500783.8	5.00/3.75	187.00	8.00/8.00	7/8	3.8	0.016	0.006	-0.004	-0.015	-0.035	0.019	0.009	-0.001	-0.012	-0.032	0.010	178.00	172.25	0.163	2.945	2.750	2.375 HEF Modified	283
	AT500784.5 SX	5.00/3.75	229.25	8.00/8.00	7/8	4.5	-0.001	-	-0.021	-	-	0.002	-	-0.018	-	-	0.010	220.00	214.30	0.172	3.091	2.750	2.375 HEF Modified	381
	AT500785.0 RM	5.00/3.88	198.00	8.00/8.00	7/8	5.0	0.003	-0.007	-0.017	-0.027	-0.037	0.005	-0.005	-0.015	-0.025	-0.035	0.010	186.00	180.00	0.171	3.041	2.750	2.375 HEF Modified	311
	AT500785.0 WF	5.00/3.88	198.00	8.00/8.00	7/8	5.0	0.001	-0.009	-0.019	-0.029	-	0.003	-0.007	-0.017	-0.027	-	0.010	186.00	180.00	0.169	3.041	2.750	2.375 HEF Modified	316
	AT500786.4	5.00/3.88	235.00	8.00/8.00	7/8	6.4	-	-0.008	-	-	-	-	-0.005	-	-	-	0.010	226.00	220.00	0.170	3.029	3.250	1.375-6 SA	372
AT500788.2	5.00/4.00	250.00	16.00/8.00	7/8	8.2	0.002	-	-0.019	-0.027	-0.041	0.004	-	-0.016	-0.024	-0.038	0.010	235.00	228.50	0.173	3.354	3.400	2.375 HEF Modified	488	
AT500896.0	5.00/4.00	250.00	8.00/8.00	8/9	6.0	-0.011	-	-	-	-	-0.006	-	-	-	-	0.010	241.00	235.00	0.163	3.198	3.380	1.375-6 SA	447	
6 1/4"	AT625782.8	6.25/5.00	130.00	8.00/8.00	7/8	2.8	0.010	-	-	-	-	0.012	-	-	-	-	0.011	117.00	110.00	0.226	3.980	3.500	2.375 API REG	335
	AT625782.9 ESX	6.25/5.00	228.75	8.00/8.00	7/8	2.9	0.000	-0.013	-0.025	-	-	0.004	-0.009	-0.021	-	-	0.011	220.75	214.25	0.233	4.204	4.000	2.375 API REG	712
	AT625783.0 SLOW	6.25/5.00	204.00	8.00/8.00	7/8	3.0	0.000	-	-0.025	-	-	0.004	-	-0.021	-	-	0.011	190.00	183.50	0.230	4.120	4.000	2.375 API REG	547
	AT625783.3 ESX	6.25/5.00	260.00	8.00/8.00	7/8	3.3	0.000	-0.013	-0.025	-	-	0.004	-0.009	-0.021	-	-	0.011	252.00	245.50	0.233	4.204	4.000	2.375 API REG	812
	AT625784.8	6.25/5.00	203.25	8.00/8.00	7/8	4.8	0.010	-0.003	-0.019	-0.028	-	0.012	-0.001	-0.017	-0.026	-	0.011	194.25	187.75	0.226	3.980	3.500	2.375 API REG	554
6 1/2"	AT650457.0	6.50/5.50	210.00	7.50/7.50	4/5	7.0	0.007	-0.003	-0.019	-0.034	-0.049	0.011	0.001	-0.015	-0.030	-0.045	0.015	202.50	195.50	0.355	4.220	4.000	2.875 API REG	576
	AT650565.4	6.50/5.31	212.00	8.00/8.00	5/6	5.4	0.000	-0.018	-0.025	-	-	0.004	-0.014	-0.021	-	-	0.010	203.00	196.00	0.297	4.158	4.000	2.875 API REG	601
	AT650568.2	6.50/5.50	246.00	11.00/11.00	5/6	8.2	0.012	0.003	-0.011	-0.026	-	0.016	0.007	-0.007	-0.024	-	0.010	233.00	226.00	0.335	4.371	4.500	2.875 SLIMLINE H-90	717
	AT650675.0	6.50/5.50	200.00	7.25/7.25	6/7	5.0	0.001	-0.014	-0.023	-0.034	-0.045	0.006	-0.009	-0.020	-0.031	-0.041	0.013	194.00	188.00	0.288	4.316	4.000	2.875 API REG	608
	AT650676.0	6.50/5.50	250.00	8.00/8.00	6/7	6.0	0.001	-0.014	-0.023	-0.034	-	0.006	-0.009	-0.020	-0.031	-	0.013	242.00	236.00	0.288	4.316	4.000	2.875 API REG	759
	AT650782.1 ESX	6.50/5.31	230.00	9.00/9.00	7/8	2.1	-0.009	-0.025	-0.035	-	-	-0.007	-0.023	-0.033	-	-	0.013	221.00	213.00	0.224	4.265	4.000	2.875 API REG	743
	AT650782.8	6.50/5.00	130.00	8.00/8.00	7/8	2.8	0.010	-	-	-	-	0.012	-	-	-	-	0.011	117.00	110.00	0.226	3.980	3.500	2.375 API REG	335
	AT650782.9 ESX	6.50/5.00	228.75	8.00/8.00	7/8	2.9	0.000	-0.013	-0.025	-	-	0.004	-0.009	-0.021	-	-	0.011	220.75	214.25	0.233	4.204	4.000	2.375 API REG	712
AT650782.9 HTS	6.50/5.50	220.00	8.00/8.00	7/8	2.9	-0.004	-0.017	-0.027	-0.037	-	-0.002	-0.015	-0.025	-0.035	-	0.013	213.50	206.50	0.244	4.296	4.000	2.875 API REG	700	

Size	Model	STATOR															ROTOR							
		CONFIGURATION					FIT @ 75° F (Inch)										Minor Diameter Tolerance +/-	CONFIGURATION						
		Tube OD/ID Inch	Length Inch	Cutback Inch	Lobes	Stages	NBR					NBR - HPW/HPX						Overall Length Inch	Contour Length Inch	Ecc Inch	Major Diameter Inch	Head Diameter Inch	Thread Connection	Weight lb
6 1/2"	AT650783.0	6.50/5.50	125.00	8.00/8.00	7/8	3.0	0.014	-0.001	-0.013	-0.020	-	0.019	0.004	-0.008	-0.017	-	0.011	118.50	111.50	0.256	4.520	4.000	2.875 API REG	435
	AT650783.0 (6.25) SLOW	6.50/5.00	204.00	8.00/8.00	7/8	3.0	0.000	-	-0.025	-	-	0.004	-	-0.021	-	-	0.011	190.00	183.50	0.230	4.120	4.000	2.375 API REG	547
	AT650783.0 SLOW	6.50/5.50	204.00	7.50/7.50	7/8	3.0	-0.010	-0.018	-0.018	-0.030	-	-0.006	-0.014	-0.014	-0.026	-	0.011	197.50	191.00	0.255	4.570	4.000	2.875 API REG	754
	AT650783.3 ESX	6.50/5.00	260.00	8.00/8.00	7/8	3.3	0.000	-0.013	-0.025	-	-	0.004	-0.009	-0.021	-	-	0.011	252.00	245.50	0.233	4.204	4.000	2.375 API REG	812
	AT650783.3 HTS	6.50/5.50	245.00	8.00/8.00	7/8	3.3	-0.004	-0.015	-0.025	-0.035	-	0.000	-0.011	-0.021	-0.031	-	0.012	238.50	231.50	0.255	4.500	4.000	2.875 API REG	877
	AT650784.8	6.50/5.00	203.50	8.00/8.00	7/8	4.8	0.010	-0.003	-0.019	-0.028	-	0.012	-0.001	-0.017	-0.026	-	0.011	194.25	187.75	0.226	3.980	3.500	2.375 API REG	554
	AT650785.0	6.50/5.50	194.50	8.00/8.00	7/8	5.0	0.014	-0.001	-0.013	-0.020	-0.031	0.019	0.004	-0.008	-0.017	-0.028	0.011	188.00	181.00	0.256	4.520	4.000	2.875 API REG	694
	AT650786.0	6.50/5.50	235.00	8.00/8.00	7/8	6.0	0.014	-0.001	-0.013	-0.020	-0.031	0.019	0.004	-0.008	-0.017	-0.028	0.011	223.00	216.00	0.256	4.520	4.500	2.875 API REG	831
AT650786.4	6.50/5.50	245.00	8.00/8.00	7/8	6.4	0.014	-0.001	-0.013	-0.020	-	0.019	0.004	-0.008	-0.017	-	0.011	238.50	231.50	0.256	4.520	4.000	2.875 API REG	883	
6 3/4"	AT675457.0	6.75/5.50	210.00	7.50/7.50	4/5	7.0	0.007	-0.003	-0.019	-0.034	-0.049	0.011	0.001	-0.015	-0.030	-0.045	0.015	202.50	195.50	0.355	4.220	4.000	2.875 API REG	576
	AT675565.4	6.75/5.31	212.00	8.00/8.00	5/6	5.4	0.000	-0.018	-0.025	-	-	0.004	-0.014	-0.021	-	-	0.010	203.00	196.00	0.297	4.158	4.000	2.875 API REG	601
	AT675568.2	6.75/5.50	246.00	11.00/11.00	5/6	8.2	0.012	0.003	-0.011	-0.026	-	0.016	0.007	-0.007	-0.024	-	0.010	233.00	226.00	0.335	4.371	4.500	2.875 SLIMLINE H-90	717
	AT675675.0	6.75/5.50	200.00	7.25/7.25	6/7	5.0	0.001	-0.014	-0.023	-0.034	-0.045	0.006	-0.009	-0.020	-0.031	-0.041	0.013	194.00	188.00	0.288	4.316	4.000	2.875 API REG	608
	AT675676.0	6.75/5.50	250.00	8.00/8.00	6/7	6.0	0.001	-0.014	-0.023	-0.034	-	0.006	-0.009	-0.020	-0.031	-	0.013	242.00	236.00	0.288	4.316	4.000	2.875 API REG	759
	AT675782.1 ESX	6.75/5.31	230.00	9.00/9.00	7/8	2.1	-0.009	-0.025	-0.035	-	-	-0.007	-0.023	-0.033	-	-	0.013	221.00	213.00	0.224	4.265	4.000	2.875 API REG	743
	AT675782.9 HTS	6.75/5.50	220.00	8.00/8.00	7/8	2.9	-0.004	-0.017	-0.027	-0.037	-	-0.002	-0.015	-0.025	-0.035	-	0.013	213.50	206.50	0.244	4.296	4.000	2.875 API REG	700
	AT675783.0	6.75/5.50	125.00	8.00/8.00	7/8	3.0	0.014	-0.001	-0.013	-0.020	-	0.019	0.004	-0.008	-0.017	-	0.011	118.50	111.50	0.256	4.520	4.000	2.875 API REG	435
	AT675783.0 SLOW	6.75/5.50	204.00	7.50/7.50	7/8	3.0	0.002	-0.010	-0.018	-0.030	-	0.006	-0.006	-0.014	-0.026	-	0.011	197.50	191.00	0.255	4.570	4.000	2.875 API REG	685
	AT675783.3 HTS	6.75/5.50	245.00	8.00/8.00	7/8	3.3	-0.004	-0.015	-0.025	-0.035	-	0.000	-0.011	-0.021	-0.031	-	0.012	238.50	231.50	0.255	4.500	4.000	2.875 API REG	877
	AT675785.0	6.75/5.50	194.50	8.00/8.00	7/8	5.0	0.014	-0.001	-0.013	-0.020	-0.031	0.019	0.004	-0.008	-0.017	-0.028	0.011	188.00	181.00	0.256	4.520	4.000	2.875 API REG	694
	AT675785.7 SX	6.75/5.50	260.00	8.00/8.00	7/8	5.7	0.003	-0.007	-0.024	-0.037	-	0.005	-0.005	-0.023	-0.035	-	0.012	252.00	245.00	0.246	4.644	4.500	2.875 API REG	1002
	AT675786.0	6.75/5.50	235.00	8.00/8.00	7/8	6.0	0.014	-0.001	-0.013	-0.020	-0.031	0.019	0.004	-0.008	-0.017	-0.028	0.011	223.00	216.00	0.256	4.520	4.500	2.875 API REG	831
	AT675786.4	6.75/5.50	245.00	8.00/8.00	7/8	6.4	0.014	-0.001	-0.013	-0.020	-	0.019	0.004	-0.008	-0.017	-	0.011	238.50	231.50	0.256	4.520	4.000	2.875 API REG	883
AT6759102.1	6.75/5.50	81.00	8.00/8.00	9/10	2.1	0.008	-	-0.015	-	-	0.012	-	-0.011	-	-	0.013	75.00	68.00	0.194	4.312	4.300	2.875 API IF	261	
7"	AT7006711.4	7.00/5.75	275.00	10.00/10.00	6/7	11.4	-0.004	-	-0.031	-	-	0.000	-	-0.027	-	-	0.013	267.00	259.00	0.306	4.689	4.500	2.875 SLIMLINE H-90	896
	AT700676.5	7.00/5.75	275.00	8.00/8.00	6/7	6.5	0.001	-0.012	-0.025	-	-	0.005	-0.008	-0.021	-	-	0.013	267.00	259.00	0.302	4.747	4.750	2.875 SLIMLINE H-90	932
	AT700678.4	7.00/5.75	275.00	8.00/8.00	6/7	8.4	0.001	-0.012	-0.024	-	-0.049	0.005	-0.008	-0.020	-	-0.045	0.013	267.00	259.00	0.302	4.747	4.750	2.875 SLIMLINE H-90	932
	AT700786.8	7.00/5.75	246.00	11.00/11.00	7/8	6.8	-0.002	-	-0.025	-	-	0.002	-	-0.021	-	-	0.011	233.00	226.00	0.250	4.538	4.500	2.875 SLIMLINE H-90	877
7 3/4"	AT775455.3	7.75/6.25	228.00	8.00/8.00	4/5	5.3	-0.001	-0.014	-0.026	-0.039	-	0.003	-0.010	-0.022	-0.035	-	0.012	221.00	213.00	0.415	4.940	4.750	3.50 API IF	856
	AT775782.2	7.75/6.25	228.00	8.00/8.00	7/8	2.2	-0.001	-	-	-	-	0.003	-	-	-	-	0.013	221.00	213.00	0.278	5.075	4.750	3.50 API IF	1043
	AT775782.5 SLOW	7.75/6.25	254.00	8.00/8.00	7/8	2.5	0.008	-0.008	-0.023	-0.037	-0.053	0.011	-0.003	-0.018	-0.034	-0.048	0.013	246.00	239.00	0.300	5.141	4.630	3.50 API REG	1157
	AT775784.0	7.75/6.25	203.25	8.00/8.00	7/8	4.0	0.008	-0.007	-0.022	-0.037	-	0.013	-0.002	-0.017	-0.032	-	0.013	196.25	188.25	0.293	5.186	4.750	3.50 API REG	956

Size	Model	STATOR															ROTOR							
		CONFIGURATION					FIT @ 75° F (Inch)										Minor Diameter Tolerance +/-	CONFIGURATION						
		Tube OD/ID Inch	Length Inch	Cutback Inch	Lobes	Stages	NBR					NBR - HPW/HPX						Overall Length Inch	Contour Length Inch	Ecc Inch	Major Diameter Inch	Head Diameter Inch	Thread Connection	Weight lb
							STD	.50S	10S	1.50S	20S	STD	.50S	10S	1.50S	20S								
8"	AT800455.3	8.00/6.25	228.00	8.00/8.00	4/5	5.3	-0.001	-0.014	-0.026	-0.039	-	0.003	-0.010	-0.022	-0.035	-	0.012	221.00	213.00	0.415	4.940	4.750	3.50 API IF	856
	AT800674.0	8.00/6.25	206.00	8.00/8.00	6/7	4.0	0.003	-	-0.032	-	-	0.006	-	-0.029	-	-	0.012	199.00	192.00	0.336	4.958	4.750	3.50 API IF	809
	AT800782.2	8.00/6.25	228.00	8.00/8.00	7/8	2.2	-0.001	-	-	-	-	0.003	-	-	-	-	0.013	221.00	213.00	0.278	5.075	4.750	3.50 API IF	1043
	AT800782.5 SLOW	8.00/6.25	254.00	8.00/8.00	7/8	2.5	0.008	-0.008	-0.023	-0.037	-0.053	0.011	-0.003	-0.018	-0.034	-0.048	0.013	246.00	239.00	0.300	5.141	4.630	3.50 API REG	1157
	AT800783.0	8.00/6.25	160.00	8.00/8.00	7/8	3.0	0.014	-	-	-	-	0.017	-	-	-	-	0.013	153.00	145.00	0.293	5.186	4.750	3.50 API REG	745
	AT800783.4 ESX	8.00/6.25	300.00	8.00/8.00	7/8	3.4	-0.015	-0.030	-0.045	-	-	-0.011	-0.026	-0.041	-	-	0.013	293.00	285.00	0.291	5.307	4.750	3.50 API IF	1377
	AT800784.0	8.00/6.25	203.25	8.00/8.00	7/8	4.0	0.008	-0.007	-0.022	-0.037	-	0.013	-0.002	-0.017	-0.032	-	0.013	196.25	188.25	0.293	5.186	4.750	3.50 API REG	956
	AT800785.9	8.00/6.25	300.00	15.50/8.00	7/8	5.9	0.008	-	-	-	-	0.013	-	-	-	-	0.013	284.50	276.50	0.293	5.186	4.750	3.50 API REG	1388
AT800896.0	8.00/6.50	206.00	8.00/8.00	8/9	6.0	0.006	-	-	-	-	0.010	-	-	-	-	0.013	192.00	185.00	0.273	5.459	4.750	3.50 API IF	1039	
9 5/8"	AT962565.0	9.63/7.88	232.00	10.00/10.00	5/6	5.0	-0.009	-	-0.034	-	-	-0.005	-	-0.030	-	-	0.019	222.00	213.00	0.472	6.296	5.500	4.00 API FH	1410
	AT962675.0	9.63/7.88	218.00	8.00/8.00	6/7	5.0	0.008	-	-0.030	-	-	0.011	-	-0.028	-	-	0.019	202.00	195.00	0.428	6.403	5.500	4.00 API FH	1378
	AT962785.7	9.63/7.88	240.00	10.00/10.00	7/8	5.7	0.003	-	-	-	-	0.005	-	-	-	-	0.019	230.88	222.00	0.354	6.373	5.500	4.00 API FH	1651
11 1/4"	AT1125564.6	11.25/9.25	230.00	10.50/10.50	5/6	4.6	0.008	-	-	-	-	0.011	-	-	-	-	0.019	219.50	210.50	0.538	7.498	6.500	Blank	1876
	AT1125565.0	11.25/7.88	232.00	10.00/10.00	5/6	5.0	-0.009	-	-0.034	-	-	-0.005	-	-0.030	-	-	0.019	222.00	213.00	0.472	6.296	5.500	4.00 API FH	1410
	AT1125675.0	11.25/7.88	218.00	8.00/8.00	6/7	5.0	0.008	-	-0.030	-	-	0.011	-	-0.028	-	-	0.019	202.00	195.00	0.428	6.403	5.500	4.00 API FH	1378
	AT1125785.7	11.25/7.88	240.00	10.00/10.00	7/8	5.7	0.003	-	-	-	-	0.005	-	-	-	-	0.019	230.88	222.00	0.354	6.373	5.500	4.00 API FH	1651